NEXIS

Box Studio Lite

Model : YS-SW41S



Specification

Model	YS-SW41S
Max. FPS	1920×1080p@300fps(4 SDI + 1 PGM Channels)
Recording Mode	Hardware Compression
Product Photo	
Input Interfaces	● Video ➢ 4×SDI ● Audio ➢ 4×3.5mm
Output Interface	● Video ➢ 1×HDMI (Multiview / PGM) ➢ 1×SDI (PGM) ● Audio ➢ 1×3.5mm
Video Feature	● H.264 /AVC, baseline/main/high profile Configurable Bit Rate Up to 64Mbps ● Support input / output resolutions ➢ 1920×1080(P60/P50/P30/P25/P24/i60/i50) ➢ 1280×720 (P60/P50) ● Support Output Resolutions:Resize Range from ➢ 160×120 to 1920×1080 (P60)
Audio Feature	● AAC-LC ● Configurable bit rate range from 32Kbps to 384Kbps ● Sample rate : 48KHz, 16bit
Network Feature	● 1×RJ45 for 10/100/1000Mbps Ethernet ● DHCP client
Support Streaming protocol	● RTSP over UDP/TCP/Multicast/HTTP ● RTMP (Publish) ● TS over IP ● HLS
Misc. Features	● Web UI for system configuration ● Firmware upgradable ● LED indicator

	● Status with Power Recycle ● Main function switch ➢ Record ➢ Snapshot ➢ Stream ● PGM mode switch ➢ Full screen ➢ Quadview ➢ Picture by picture ➢ Picture in picture ➢ PGM Loop ● Full screen switch ➢ Channel 1 ➢ Channel 2 ➢ Channel 3 ➢ Channel 4 ● 2×USB2.0 (For Keyboard and mouse usage) ● 1×USB3.0 (For external storage usage) ● 1×RS232 + 1×RS485
Record Format	MP4 / TS / AVI / MOV