NEXIS

CV138D

USB3. 0 TO HDMIX2Port Adapter

Support MST function



Product Name: USB 3.0 TO Dual HDMI Hub Video Converter
Product Class: Audio and video signal converter
Product size: Φ70*11mm; cable length: 150mm input: USB3.0 female
product function: This product can transfer Video and Audio from USB3.0 port device to dual HDMI.Product work through internal chipset Silicon Motion-SM768. While two HDMI port work together, one port can meet 1920*1080@60Hz and other one can meet 3840*2160@30Hz. This product can work with two different screen(MST function) and same screen(mirror function).
Please check below link to download SM76X driver before use this product
http://www.siliconmotion.com/downloads/index.html
It support Windows 8.1, 10, 11 , Mac OS 10.10 above, Mac M1, M2, M3, M4, Intel CPU and Android system.

Signal input/output: Input port:USB 3.0 signal source
The power port: USB 3.0 port
The output port:HDMI*2port(1080/4k@30Hz)
Product Features: It has small body, thin enough. Aluminum housing and ABS bottom with silicon pad to ensure product won't move while using. Product use Silicon Motion's chipset, with strong stability and compatibility. Easy to use, easy to connect, one time load driver, no worry to use. Dual HDMI can extend to three screens,or the same screen signal, or signal expansion.
Product Application: The product is widely used in the main device with USB3.0 interface port and HDMI interface port for the display equipment. It has dual video output, also can host external video expansion. User don't need complicated operation.

Other Features: The product is made of environment-friendly materials, and the connector part is copper with gold/nickel plating. This product has more aesthetic feeling and texture, it needs to install the drive in first time. Meanwhile, It can perfectly support MST function and Mirror function of Mac OS system and WIN system, Rotate 90º Screen in Windows & Mac

Input and output characteristics: the input port can support USB3.0 standard interface,The HDMI port can output 1920*1080@60Hz and 3840*2160@30Hz.The product has a built-in driver, the product needs to be connected to the boot installation, and the product only needs to be installed once



USB3.0 TO HDMI X2Port ADAPTER

Signal input/output	
Input port Output port	USB 3.0 HDMI Female(1.4)/HDMI(1.3)Female
Support input port	Support USB3.0 port (Equipment with Video output function
	Video port:480p,720p,1080p,etc.HDMI Support output 1920*1080@60Hz
Working Frequency	
Video output frequency Data output frequency	Video working broadband:5.4Gps-10Gps
Environmental parameters	
Working temperature Working humidity Storage temperature Store humidity	0℃ to +60℃ 10%-85RH -10℃ to +80℃ 5%-90%RH
The warranty period	1 year
Accessory adapter	
Cable Weight Product size	-- 55g 70*11mm