MK822C

(HDMI KVM Switch, 2ports,Dual-View）



As a KVM switch 2 ports with HDMI interface allows users to access from a single USB keyboard, mouse and HDMI the display console accesses 2 computers. Desktop compact design, metal casing, easy to install and place; provide users with a variety of fast switching options for audio, video, USB devices, saving desktop space, is a multimedia application such as SOHO office Ideal.

Features:

- 2 port USB2.0 multiple video series KVM switch
- Single USB controls 2 sets of computers and peripherals USB
- Built-in USB3.0 , compatible with USB protocol specification
- HDMI video maximum support resolution is 4K@ 60fp
- Provide keyboard hot-key switching shortcut function and device panel button two switching function selection
- Support multiple platforms for various operating systems
- BIOS level hardware connection, no need to install drivers and control software
- The front panel of the device is extended with a USB interface, which is convenient for users to connect peripheral devices such as a USB keyboard, a mouse, or a USB flash drive or a USB printer .
- Provide a variety of hot-key selection and setting functions, so that users can set their own hot-keys according to the situation.
- Automatically scans the connected computer

Specification:

Features			MK822C
Computer connections			2
Port selection			Front panel buttons/Hot-key
Connector	Control port	monitor	1 x HDMI Type A black Female
		keyboard	1 x USB Type A female
		mouse	1 x USB Type A female
		speaker	1 x Mini stereo jack female(green)
		microphone	1 x Mini stereo jack female(pink)
		USB3.0	2 x USB3.0 Type A Blue Female
	Computer port	monitor	4 x HDMI Type A female (black)
		keyboard and mouse	2 x USB Type B female (white)
		speaker & microphone	2 x Mini stereo jack female (black)
	power		1 x DC socket
Toggle switch	KVM switch button		2 x button
LED’s	online		2 x red
	Selected		2 x green
Analog mode	Keyboard and mouse		USB
Maximum resolution video			4K@60HZ(3840x2160 @30HZ)
Hot-key			CTL+CTL
Operating environment	Operating temperature		0-50 °C
	Storage temperature		-20-60 °C
	Humidity		0-80% RH , no condensation
Housing	House		metal
	Size		132 x 92 x 66mm
	Weight		0.58Kg