4K@60 HDMI Switcher 4×1

HSW41A



Features

- Compliant with HDMI 2.0a, DVI 1.0 standards.
- HDCP 2.2 and HDCP 1.4 compliant.
- Video formats up to 4Kx2K@60 and all HDMI 3D video formats.
- Support PCM, Dolby TrueHD, DTS-HD Master Audio up to 7.1CH
- Digital and analog audio output
- Support smart EDID management(Auto/2CH/5.1CH/7.1CH selectable)
- Support input port auto switching or manual switching mode
- Audio Return Channel (ARC) supports

Specifications

Frequency Bandwidth	18Gbps
Input Ports	4 HDMI Female ports, 1 IR Receive port and 1 RS232 port
Output port	1 HDMI Female port and 1 L/R & Optical port
HDMI Audio Output	PCM2.1/5.1/7.1CH, Dolby 5.1, DTS5.1, Dolby-TrueHD, DTS-HD
ESD Protection	Human Body Model:± 8kV (air-gap discharge) ± 4kV (contact discharge)
Dimensions (mm)	180 (D) x 85 (W) x 11.6 (H)
Weight (g)	300
Power Consumption	Max 2.5W
Operating Temperature	0˚C ~ 40˚C / 32˚F ~ 104˚F
Storage Temperature	-20˚C ~ 60˚C / -4˚F ~ 140˚F

Application Example

